

MODEL “AS-III” RETRIEVABLE PACKER

DESCRIPTION

The Model AS-III Packer is a single-grip packer with no upper hold-down for use where no differential pressure from below is present. From the packing elements down, the AS-III Packer operates identically to the AS-II Packer. The AS-III Packer also features a large by-pass area to prevent swabbing when running for retrieving. The AS-III Packer is ideal for isolating casing holes or perforations when used as the lower packer in conjunction with the Snapset II Packer as the upper packer and becomes in an excellent straddle system.

FEATURES

- Large internal by-pass
- 1/4 turn set / straight pick-up release
- Additional J-slot arrangements available

PRODUCT SPECIFICATION

Size (inches)	Casing		Recommended Hole Size (inches)	Tool OD (inches)	Tool ID (inches)	Thread Connection Box Up/Pin Down
	Weight (lbs/ft)					
3-1/2	7.7-10.2		2.922 - 3.068	2.781	1.25	1.900 NUE
4-1/2	9.5-13.5		3.920 - 4.090	3.750	1.94	2-3/8 EUE
5	11.5-15		4.408 - 4.560	4.125	1.94	2-3/8 EUE
5-1/2	14-20		4.778 - 5.012	4.625	1.94	2-3/8 EUE
					2.38	2-7/8 EUE
	20-23		4.670 - 4.778	4.500	2.00	2-3/8 EUE
6-5/8	17-24		5.921 - 6.135	5.750	2.50	2-7/8 EUE
	24-32		5.675 - 5.921	5.500	2.50	2-7/8 EUE
7	17-26		6.276 - 6.538	6.000	2.50	2-7/8 EUE
	26-32		6.094 - 6.276	5.875	2.50	2-7/8 EUE
					3.00	3-1/2 EUE
7-5/8	24-29.7		6.875 - 7.025	6.672	2.50	2-7/8 EUE
8-5/8	28-40		7.725 - 8.017	7.500	4.00	3-1/2 EUE
9-5/8	32.3-43.5		8.755 - 9.001	8.500	4.00	3-1/2 EUE
	43.5-53.5		8.535 - 8.755	8.250	2.50	2-7/8 EUE

