

# TANDEM TENSION PACKER MODEL DL-1B

## DESCRIPTION

The Type DL-1B Tandem Tension Packer is an economical, compact, low-pressure, tension set, isolation packer used in casing or perforations and multi-zone injection installations. This packer runs with a tension set packer below. It can be run with the J-pins in the un-jayed position or in the jayed position. In the un-jayed position, applying tension shears the shear pins and allows pack-off.

If run in the jayed position, the DL-1B Tandem Tension Packer must be used in conjunction with an ASI-X, Shear Tension or LokSet Packer. Set down weight shears the pins; left-hand rotation and applied tension will set the tool.

## FEATURES AND BENEFITS

- Economical
- Run in jayed position, or un-jayed position
- Optional J-configurations

## PRODUCT SPECIFICATION

Casing		Recommended Hole Size (inches)	Tool OD (inches)	Tool ID (inches)	Thread Connections Box Up / Pin Down
Size (inches)	Weight (lbs/ft)				
4-1/2	9.5 - 11.6	4.000 - 4.090	3.844	1.94	2-3/8 EUE
				2.38	2-7/8 EUE
	9.5 - 13.5	3.920 - 4.090	3.750	1.50	2-3/8 EUE
				1.94	2-3/8 EUE
	15.1	3.826	3.650	1.94	2-3/8 EUE
5	15.0 - 18.0	4.276 - 4.408	4.125	1.94	2-3/8 EUE
				2.38	2-7/8 EUE
	18.0 - 20.8	4.156 - 4.276	4.000	1.94	2-3/8 EUE
5-1/2	13.0 - 15.5	4.950 - 5.044	4.781	2.00	2-3/8 EUE
				2.44	2-7/8 EUE
	13.0 - 20.0	4.778 - 5.044	4.750	3.00	3-1/2 EUE
	15.5 - 20.0	4.778 - 4.950	4.641	2.00	2-3/8 EUE
				2.44	2-7/8 EUE
7	15.5 - 23.0	4.670 - 4.950	4.500	2.00	2-3/8 EUE
	17.0 - 23.0	6.366 - 6.538	6.125	2.00	2-3/8 EUE
				2.44	2-7/8 EUE
	17.0 - 26.0	6.276 - 6.538	6.000	3.00	3-1/2 EUE

NOTE: All pricing includes standard Nitrile trim. Other sizes and connections available upon request.

