

MODEL “GR” BOTTOM NO-GO SEATING NIPPLE

DESCRIPTION

The Well Intervention Services Model “GR” Bottom No-Go Non-Ported Seating Nipple is a tubing nipple for use with bottom no-go locking devices only. It has a seal bore, bottom no-go shoulder, and a locking groove. The Model “GR” nipple locates, seals, and retains flow control accessories that have a bottom no-go locking device. The accessories are run and retrieved on wireline. “GR” Seating Nipples are typically located at the bottom of the tubing string as the last profile, with only a wireline re-entry guide lower in the tubing string.

Caution must be taken if placing a “GR” Bottom No-Go Seating Nipples at any point other than the last profile in the tubing string to ensure clearance for the passage of wireline tools to Seating Nipple profiles below the “GR” Bottom No-Go Seating Nipple.

BENEFITS

- The Bottom No-Go ensures simple and positive landing of wireline tools.
- The Bottom No-Go prevents the loss of wireline tools when they are inadvertently dropped or released during running or retrieving.

PRODUCT SPECIFICATION

Baker®-Style “GR” Bottom No-Go Landing Nipple							
TUBING O.D.		SEAL BORE		NO-GO I.D.		MIN O.D.* Box by Pin Threads	
in.	mm.	in.	mm.	in.	mm.	in.	mm.
1.660	42.15	1.187	30.15	1.135	28.83	1.875	47.63
		1.250	31.75	1.198	30.43		
1.900	48.26	1.437	36.50	1.385	35.18	2.109	53.57
		1.500	38.10	1.447	36.75		
2-1/16"	53.37	1.562	39.67	1.510	38.35	2.250	57.15
		1.625	41.28	1.572	39.93		
2-3/8"	60.33	1.781	45.24	1.728	43.89	2.560	65.02
		1.812	46.02	1.760	44.70		
		1.875	47.63	1.822	46.28		
2-7/8"	73.02	2.062	52.37	1.965	49.91	3.109	78.97
		2.125	53.98	2.035	51.69		
		2.250	57.15	2.197	55.80		
		2.312	58.72	2.259	57.38		
3-1/2"	88.90	2.562	65.07	2.442	62.03	3.687	93.65
		2.750	69.85	2.697	68.50		
		2.812	71.42	2.759	70.08		

