

# MODEL GV CUP PACKER

## DESCRIPTION

The model “GV” Cup Packer is an economical means of isolating casing leaks and depleted zones and is also a production or injection packer for low pressure applications. Depending on the application, this packer can be run with opposed cups or in the same direction.

The GV Cup Packer is also available with packing element back-up rings for high pressure applications and comes in a full range of tubing and casing sizes in two-cup, three-cup or four-cup models.

## FEATURES

- Economic Design
- Cup direction option
- Tubing and casing sizes

## PRODUCT SPECIFICATION

Size (inches)	Casing		Recommended Hole Size (inches)	Tool OD (inches)	Tool ID (inches)	Thread Connection Box Up/Pin Down
	Weight (lbs/ft)					
3-1/2	9.2-10.3		2.922 - 2.992	2.810	1.50	1.900 NUE
4-1/2	9.5-13.5		3.920 - 4.090	3.750	2.00	2-3/8 EUE
					2.50	2-7/8 EUE
	15.1		3.826	3.650	2.00	2-3/8 EUE
5	18		4.276	4.130	2.00	2-3/8 NUE
7	20-29	6.184 - 6.456	6.000	6.000	2.00	2-3/8 EUE
					2.50	2-7/8 EUE
					3.00	3-1/2 EUE
					4.00	4-1/2 LTC
9-5/8	40-47		8.681 - 8.835	8.450	3.00	3-1/2 EUE

